



PRODUCT DESCRIPTION:

TraffiDeck ED is a thick coating system with multiple layers builtup which provides protection against sun, water and thermal movements. It also protects floor from oil and acids.

USES:

- New or old construction
- Levels entire floors, featheredge to deepfill
- Resurfaces old damaged concrete floors
- Water resistant
- Caps cracked, lightweight concrete
- Installs above and on grade
- Experienced, authorized applicators all over India
- Exceeds standards set by leading floor goods manufacturers

SYSTEM DATA:

TraffiDeck ED Primer	Primer coat	FloorPrime PU
TraffiDeck ED Membrane	Waterproofing Layer	Multithane
TraffiDeck ED Body Coat	PU Flooring	FloorThane 200
TraffiDeck ED Quartz	Quartz Sprinkle	OxideFill-5
TraffiDeck ED Topcoat	PU Top Coat	Armouthane TC90

APPLICATION DATA:

Installation

Preparation — Concrete subfloors must be fully cured, moisture free, and have no efflorescence. The substrate surface shall be clean, dust and contaminant free. Cracks should be filled with a crack filler, based on Floorcrete Floor crack repair. Plumbing or electrical penetrations should be packed with insulation and sealed.

Subfloor — All subfloors must be structurally sound, solid, free of dirt, mud, dust, grease, curing and sealing compounds, and other contaminating factors. All subfloors must be dry and a minimum of 10 °C. Mechanically clean the surface by shotblasting or scarifying. Shotblast to an IRCI Concrete Surface Profile 5 (CSP 5).

Priming — To promote proper hydration and to ensure a solid bond, the subfloor must be coated with Traffideck ED Floor Primer.

Mixing & Application — All products should be mixed before use. Follow detailed description as per individual data sheets.

CLEANING:





All tools should be cleaned with suitable solvent immediately after use.

STORAGE:

Store in dry, frost-free conditions at moderate temperatures not greater than 25 °c.

WARRANTY

Multichem warrants Traffideck products to be free from manufacturing defects as defined in this warranty. Manufacturing defects are considered to be those defects that occur due to the quality of the ingredients or from the manufacturing process itself. This warranty does not include labor costs and other costs or expenses associated with the removal or installation of Traffideck Products.

Because the Multichem does not perform the actual installation, it cannot be held responsible for the results of the application. Multichem specifically disclaims problems that occur due to weather conditions, structural movement, structural design flaws and application techniques.

This warranty is in lieu of all other warranties expressed or implied including the warranty of merchantability and fitness of purpose and of all other obligations or liabilities on Multichem part. Multichem neither assumes nor authorizes any person to assume for Multichem any liability in connection with the sale and installation of Traffideck products.

Because of constant improvement of manufacturing techniques and formulations, Company reserves rights to change this datasheet and its contents without prior notice.